

ORGAL ROOFLEX S6

Revision nr.4 Dated 08/08/2018 Printed on 08/08/2018 Page n. 1/9

Replaced revision:3 (Dated 18/05/2017)

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ORGAL ROOFLEX S6

Chemical name and synonym Styrene acrylic copolymer in water

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Binder for construction chemicals.

1.3. Details of the supplier of the safety data sheet

Name ORGANIK KIMYA SANAYI VE TICARET A.S.

Full address Mimarsinan Mah. Cendere Yolu No.146 Kemerburgaz/Eyüp

District and Country 34075 İstanbul Turkiye

Tel. +90 212 331 00 00 Fax +90 212 331 00 01

e-mail address of the competent person

responsible for the Safety Data Sheet msds@organikkimya.com (+90 533 603 54 90)

Product distribution by: REACH Only Representative in EU: Organik Kimya Netherlands B.V. Phone: +31 10

295 48 20 Fax: +31 10 295 48 29 Address: Chemieweg 7, havennumber 4206, 3197

KC Botlek - Rotterdam Netherlands

1.4. Emergency telephone number

For urgent inquiries refer to For Chemical Emergency (Spill, Leak, Fire, Exposure, or Accident) Call CHEMTREC

Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada:+ 1

703-527-3887 (collect calls accepted)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

EUH208 Contains: 5-Chloro-2-methyl-3(2H)-isothiazolone mixt. with 2-methyl-3(2H)-isothiazolone(CAS:

55965-84-9)

May produce an allergic reaction.

Precautionary statements: --

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.



ORGAL ROOFLEX S6

Revision nr 4 Dated 08/08/2018 Printed on 08/08/2018 Page n. 2/9

Replaced revision:3 (Dated 18/05/2017)

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

5-Chloro-2-methyl-3(2H)-isothiazolone mixt. with 2-methyl-3(2H)-isothiazolone(CAS: 55965-84-9)

CAS 55965-84-9 $0 \le x < 0.0015$

Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Skin Corr. 1B H314,

Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1,

Aquatic Chronic 1 H410 M=1

FC 611-341-5 INDEX 613-167-00-5

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent



ORGAL ROOFLEX S6

Dated 08/08/2018 Printed on 08/08/2018 Page n. 3 / 9 Replaced revision:3 (Dated 18/05/2017)

Revision nr 4

SECTION 6. Accidental release measures .../>>

any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

The emulsion must be stored between 5-25°C for a maximum of 12 months and freezing must be avoided.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Information not available

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS



ORGAL ROOFLEX S6

Revision nr.4 Dated 08/08/2018 Printed on 08/08/2018 Page n. 4 / 9 Replaced revision:3 (Dated 18/05/2017)

SECTION 8. Exposure controls/personal protection .../>>

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

GLOVES TYPE: Nitrile rubber, breakthrough time > 480 minutes, glove thickness 0.1 - 0.4 mm.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance viscous liquid Colour white Odour characteristic Odour threshold Not determined 7,5-9,0 Melting point / freezing point Not applicable Initial boiling point 100 °C Boiling range Not applicable Flash point Not applicable **Evaporation Rate** slower (ethyl ether=1) Flammability of solids and gases not flammable Lower inflammability limit Not applicable Not applicable Upper inflammability limit Lower explosive limit Not applicable Upper explosive limit Not applicable Vapour pressure Not determined Vapour density heavier (air=1) Relative density 1,0-1,1 Solubility soluble in water Partition coefficient: n-octanol/water Not determined Auto-ignition temperature Not applicable Not determined Decomposition temperature <9000 cps Viscosity not explosive Explosive properties

9.2. Other information

Oxidising properties

Molecular weight
Total solids (250°C / 482°F)
VOC (Directive 2010/75/EC):

Not determined
50.00 %
0.01 %

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

not oxidising

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available



ORGAL ROOFLEX S6

Revision nr 4 Printed on 08/08/2018 Page n. 5 / 9

Replaced revision:3 (Dated 18/05/2017)

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

STYRENE ACRYLIC COPOLYMER LD50 (Dermal/oral,rat)>5000 mg/kg.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: Not classified (no significant component) Not classified (no significant component) LD50 (Oral) of the mixture: Not classified (no significant component) LD50 (Dermal) of the mixture:

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains

5-Chloro-2-methyl-3(2H)-isothiazolone mixt. with 2-methyl-3(2H)-isothiazolone(CAS: 55965-84-9)

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class



ORGAL ROOFLEX S6

Revision nr 4 Printed on 08/08/2018

Replaced revision:3 (Dated 18/05/2017)

SECTION 11. Toxicological information .../>>

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

STYRENE ACRYLIC COPOLYMER

WGK (Water Risk Class): 1.

12.1. Toxicity

5-Chloro-2-methyl-3(2H)-isothiazolone mixt. with 2-methyl-3(2H)-isothiazolone(CAS: 55965-84-9)

LC50 - for Fish 14.8 mg/l/96h OECD 203 EC50 - for Crustacea 8 mg/l/48h OECD 202 EC50 - for Algae / Aquatic Plants 3.2 mg/l/72h OECD 201

STYRENE ACRYLIC COPOLYMER

EC50 - for Crustacea 100 mg/l/48h Daphnia magna

12.2. Persistence and degradability

STYRENE ACRYLIC COPOLYMER

This type of product is only slowly biodegraded (removal>80% by method OECD 302B).

5-Chloro-2-methyl-3(2H)-isothiazolone mixt. with 2-methyl-3(2H)-isothiazolone(CAS: 55965-84-9) Rapidly degradable

12.3. Bioaccumulative potential

STYRENE ACRYLIC COPOLYMER No bioaccumulation potential.

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable



ORGAL ROOFLEX S6

Revision nr.4 Dated 08/08/2018 Printed on 08/08/2018 Page n. 7 / 9

Replaced revision:3 (Dated 18/05/2017)

SECTION 14. Transport information .../>>

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3 Acute toxicity, category 3
Skin Corr. 1B Skin corrosion, category 1B
Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H301 Toxic if swallowed.H311 Toxic in contact with skin.H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

ORGAL ROOFLEX S6

Revision nr 4 Dated 08/08/2018 Printed on 08/08/2018

Replaced revision:3 (Dated 18/05/2017)

SECTION 16. Other information .../>>

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects. H410

EUH210 Safety data sheet available on request.

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- FCHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.



Revision nr.4 Dated 08/08/2018

Printed on 08/08/2018 Page n. 9 / 9 Replaced revision:3 (Dated 18/05/2017)

ΕN

ORGAL ROOFLEX S6

SECTION 16. Other information .../>> Changes to previous review: The following sections were modified: 01 / 02 / 03 / 04 / 07 / 08 / 09 / 11 / 15.